Bemix F4 FF - Version 2 Page 1 of 11



### **SAFETY DATA SHEET**

### **Bemix F4 FF**

The safety data sheet is in accordance with Commission Regulation (EU) 2020/878 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

# SECTION 1: Identification of the substance / mixture and of the company / undertaking

Date issued 16.11.2018

Revision date 19.12.2024

### 1.1. Product identifier

Product name Bemix F4 FF

UFI Y0A8-901F-J00A-DDJH

Article no. 1100300, 1100305, 1101640, 1101645

GTIN No. 7331933708156, 7331933714324

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Product group Construction grout.

Use of the substance / mixture A thixotropic, expanding, pumpable jointing compound. It is used for sealing and

ointing

concrete elements and granite blocks Cures in minus degrees without heating,

down to -10°C.

Main intended use PC-CON-4 Mortars

Uses advised against

The product may not be used in any other way than the intended use as

described above.

### 1.3. Details of the supplier of the safety data sheet

Company name Finja Bemix AB

Office address Finvids väg 6, Upplands Väsby

Postal address Box 421

Postcode 194 04

City Upplands Väsby

Country Sverige

Telephone number +46104559500

Email <u>info@bemix.se</u>

Website www.bemix.se

Bemix F4 FF - Version 2 Page 2 of 11

Enterprise No. 556117-3377

### 1.4. Emergency telephone number

Emergency telephone Telephone number: In case of emergency - Call 112 and request poison

information.

In less urgent cases, call 010-455 95 00, Monday-Friday 7:00 a.m. 3:30 p.m.

### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP / GHS] Skin Irrit. 2; H315

Eye Dam. 1; H318

STOT SE 3; H335

Substance / mixture hazardous properties

The product is classified as irritating to eyes, skin and by inhalation. Risk of serious eye damage. Inhaling cement dust can irritate the mucous membranes in the nose and throat. In contact with moist skin and mucous membranes, the product becomes corrosive. The product is not classified as flammable. The product is not classified as environmentally hazardous.

#### 2.2. Label elements

### **Hazard pictograms (CLP)**





Composition on the label

Portlandcement\*, Sand containing quartz (SiO2)\*\*, Sodium nitrate

Signal word

Danger

Hazard statements

H315 Causes skin irritation. H318 Causes serious eye damage. H335 May cause respiratory irritation.

Precautionary statements

P280 Wear protective gloves / protective clothing / eye protection / face protection. P362+P364 Take off contaminated clothing and wash it before reuse. P302+P352 IF ON SKIN: Wash with plenty of soap and water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. P312 Call a POISON CENTER or doctor / physician if you feel unwell.

### 2.3. Other hazards

PBT / vPvB

The product, assessed on the basis of available data, does not contain PBT substances (non-degradable/bio accumulative/toxic) or vPvB substances (very persistent and very bio accumulative) according to Regulation (EC) No. 1907/2006 (REACH) Annex XIII.

Other hazards

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated

Bemix F4 FF - Version 2 Page 3 of 11

Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

### **SECTION 3: Composition / information on ingredients**

#### 3.2. Mixtures

Composition type	Mixture			
Substance	Identification	Classification	Contents	Notes
Portlandcement*	CAS No.: 65997-15-1 EC No.: 266-043-4	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335	30 -40 %	
Sand containing quartz (SiO2) **	CAS No.: 14808-60-7 EC No.: 238-878-4		50 -70 %	
Sodium nitrate	CAS No.: 7631-99-4 EC No.: 231-554-3	Eye Irrit. 2; H319 Ox. Sol. 2; H272	1 -3 %	
Remarks, substance	an allergic skin re ** Classification of	* The Portlandcement has reduced CR (VI) and consequently H317, May cause an allergic skin reaction, is not applicable for this produkt.  ** Classification of quartz depends on the proportion of respirable crystalline quartz. Current sand does not contain respirable crystalline quartz above 1% and		talline

is therefore not classified as hazardous to health.

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

General	In case of accident or if you feel unwell seek medical advice (show label or SDS where possible).
Inhalation	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Wash nose, mouth and throat with water. IF exposed or concerned: Get medical advice/attention.
Skin contact	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

### 4.2. Most important symptoms and effects, both acute and delayed

Acute symptoms and effects	Corrosive if product is moist. May cause severe irritation ore even corrosive damage. The product may cause skin dryness. Risk of severe eye damage. Burn in throat. May cause stomach pain.	
Delayed symptoms and effects	Has an irritating effect on the mucous membranes of the respiratory tract. Long-term exposure to high concentrations of quartz can cause lung changes (silicosis).	

### 4.3. Indication of any immediate medical attention and special treatment needed

Bemix F4 FF - Version 2 Page 4 of 11

Separate first aid equipment

Eyewash must be available.

Other information

Always get medical attention if symptoms remain. Don't give anything through the mouth to an unconscious person. Follow the advice given in section

4.1.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media

Use extinguishing agents suitable for the surrounding fire.

Improper extinguishing media

No special recommendations.

### 5.2. Special hazards arising from the substance or mixture

Fire and explosion hazards

The product is not classified as flammable or combustible.

Hazardous combustion products

No information available for the product.

### 5.3. Advice for firefighters

Special protective equipment for firefighters

During all firefighting suitable protective equipment should be used. Protective suit covering the whole body and fresh air mask is recommended.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures

Avoid contact with respiratory system, skin or eyes. Use appropriate protective equipment see section 8.

### 6.2. Environmental precautions

Environmental precautionary

measures

Avoid spreading to drains and waterways.

### 6.3. Methods and material for containment and cleaning up

Containment Dry product is collected in a closed container to minimize the risk of dust

spreading.

Clean up Dry product is preferably vacuumed up with industrial vacuum cleaners. Wet

product can be scooped up.

Other information Collected material can be mixed with water for curing. Cured product is not

aggressive or reactive.

#### 6.4. Reference to other sections

Other instructions See section 7 for information on safe handling. Se section 8 for information on

personal protection equipment and section 13 for waste handling.

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Bemix F4 FF - Version 2 Page 5 of 11

Handling

Transported/handled in original packaging or in another suitable container. Mixing should take place outdoors or in well-ventilated environments.

### **Protective safety measures**

Protective safety measures

The workplace must have access to an eye wash with tempered water. Wash the skin after each shift, before meals, smoking and going to the toilet. No eating or drinking in the workplace.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage

Store dry. Corrosive when moist. To reduce the risk of sensitization due to chrome the cement contains a low amount of Cr(VI). This effect remains 6 months after the packaging date if the product is stored according to instructions. Use of the product after this recommended time limit there is an increased risk of sensitization.

### Conditions for safe storage

Requirements for storage rooms and vessels

Store in a dry place. Store in a closed container.

### 7.3. Specific end use(s)

Recommendations

See technical data sheet for additional information.

### **SECTION 8: Exposure controls / personal protection**

Comments if preventive industrial medical examinations are to be carried out

Medical control - quartz (fibrosis-causing dust) . Medical checks in working life (AFS 2019:3)

### 8.1. Control parameters

Substance	Identification	Exposure limits	TWA Year
Sand containing quartz (SiO2) **	CAS No.: 14808-60-7	Country of origin: Sverige Limit value type: NGV Limit value (8 h): 2,5 mg/ m³ Source: AFS 2018:1 Comments: 2,5 mg/m3 (respirabelt) 5,0 mg/m3 (inhalerbart)	
Dust, inorganic		Country of origin: Sweden Limit value type: NGV Limit value (8 h): 5 mg/m³ Source: AFS 2018:1 Particle fraction: Inhalable Country of origin: Sweden Limit value type: NGV Limit value (8 h): 2,5 mg/m³ Source: AFS 2018:1 Particle fraction: Respirable	

Bemix F4 FF - Version 2 Page 6 of 11

### 8.2. Exposure controls

### Safety signs









### Precautionary measures to prevent exposure

Appropriate engineering controls Avoid dusty handling. Use good general ventilation and local process ventilation

if there is a risk of dust formation.

### Eye / face protection

Suitable eye protection At risk of direct contact or splashing use tightly sealed safety glasses.

### **Hand protection**

Skin- / hand protection, short term

contact

At risk of direct contact or splashing use gloves.

Suitable materials Natural rubber, neoprene or PVC.

#### Skin protection

Suitable protective clothing Safety clothing when needed. In case of contact with wet product, waterproof

clothing and shoes should be used.

### **Respiratory protection**

Respiratory protection necessary

at

In case of brief exposure to dust use respiratory filter device with particle filter

P3. In

case of intensive or longer exposure use self-contained respiratory protective

device.

### Hygiene / environmental

Specific hygiene measures

Wash soiled clothing after use.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state Powder

Colour Gray Colour intensity Light.

Odour Slight smell

рΗ Status: In aqueous solution

Value: 12

Melting point / melting range Reason for waiving data: Not applicable

Boiling point / boiling range Reason for waiving data: Not applicable Bemix F4 FF - Version 2 Page 7 of 11

Flash point Reason for waiving data: Not applicable

Flammability Not flammable.

Vapour pressure Reason for waiving data: Not applicable Vapour density Reason for waiving data: Not applicable

Bulk density Value: 1500 ~ 1700 kg/m³

Solubility Medium: Water

Comments: Miscible with water.

Partition coefficient: n-octanol/

water

Reason for waiving data: Not applicable

Auto-ignition temperature Reason for waiving data: Not applicable Decomposition temperature Reason for waiving data: Not applicable

Viscosity Reason for waiving data: Not applicable

Explosive properties Not applicable

Oxidising properties Not applicable

#### 9.2. Other information

### Other physical and chemical properties

Physical and chemical properties

Reacts with water, forms high pH, solidifies under some (harmless) heat

development.

### 9.2.2. Other safety characteristics

Miscibility Miscible with water

Comments Cured material is no longer reactive or aggressive.

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Reacts with damp/water and forms calcium hydroxide which gives

the mixture a high pH. The product reacts with water and hardens

#### 10.2. Chemical stability

Stability The product is stable if used according to supplier instructions.

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions No known.

#### 10.4. Conditions to avoid

Conditions to avoid Avoid moisture.

#### 10.5. Incompatible materials

Bemix F4 FF - Version 2 Page 8 of 11

Materials to avoid

Avoid contact with water except when using the product according to supplier instructions.

### 10.6. Hazardous decomposition products

Hazardous decomposition products

None known.

### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Other information regarding health hazards

Assessment of acute toxicity, classification

The product is not classified as acute toxic.

Assessment of skin corrosion / irritation, classification

If the produkt is moist it can be corrosive due to the high pH and consequently there is a risk of corrosive damage at long term contact with moist product or wet skin

Assessment of eye damage or irritation, classification
General respiratory or skin

Can cause corrosive damage, both as dry powder and wet mixture.

sensitisation

May be irritating to the respiratory system and mucous membranes

Assessment of skin sensitisation, classification

The product is not classified as sensitizing. Contains traces of chrome. May  $\begin{tabular}{ll} \end{tabular} \label{table}$ 

cause

allergic effects on already sensitized (chrome allergic) persons

Inhalation Can lead to chronic problems.

Skin contact Dry skin and dry cracks. Dust can irritate the respiratory system.

Eye contact Permanent eye damage, corrosive.

Ingestion Irritating to the oral cavity, mucous membranes and digestive organs.

Sensitisation Contains traces of chromium. Which can cause allergic problems for already

sensitized people.

Assessment of germ cell mutagenicity, classification

This product is not classified as mutagen.

Assessment of carcinogenicity, classification

This product is not classified as cancerogen.

Assessment of reproductive toxicity, classification

This product is not classified as toxic for reproduction.

#### Symptoms of exposure

In case of ingestion Coughing and burning.

corrosion damage may occur.

In case of inhalation Cough and dry throat.

In case of eye contact Irritating, stinging and watery eyes. May cause pain.

#### 11.2 Other information

Bemix F4 FF - Version 2 Page 9 of 11

**Endocrine disruption** 

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

### **SECTION 12: Ecological information**

#### 12.1. Toxicity

**Ecotoxicity** 

The product is not classified as hazardous to the environment. Ecological data for the product are not available available.

### 12.2. Persistence and degradability

Persistence and degradability description/evaluation

Biodegradability is not a relevant characteristic for inorganic substances.

### 12.3. Bioaccumulative potential

Bioaccumulation, comments

No data known.

#### 12.4. Mobility in soil

Mobility

No information available for the product.

#### 12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment

The product, assessed on the basis of data, does not contain PBT substances (non-degradable/bio accumulative/toxic) or vPvB substances (very persistent and very bio accumulative) according to Regulation (EC) No. 1907/2006 (REACH) Annex XIII.

### 12.6. Endocrine disrupting properties

Endocrine disrupting properties

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

#### 12.7. Other adverse effects

Additional ecological information

Contact with water gives an pH which can be toxic for water living organisms.

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Appropriate methods of disposal for the chemical

The user is responsible for correct coding and labeling of the waste. Dispose of as special waste and in accordance with local and national regulations. Partial and residual amounts can be reused. Uncured product is classified as harmful waste but cured product is handled as construction waist.

Appropriate methods of disposal for the contaminated packaging

The waste is handled according to official and local regulations. Packaging that is not completely emptied must be treated as the unused product. The packaging should preferably be reused alt. be recycled.

EWC waste code

EWC waste code: 101314 waste concrete and concrete sludge

Bemix F4 FF - Version 2 Page 10 of 11

Classified as hazardous waste: No

EWC waste code: 200115 alkalines Classified as hazardous waste: Yes

EWL packing EWC waste code: 150102 plasticpackaging

Classified as hazardous waste: No

EWC waste code: 150106 mixed packaging

Classified as hazardous waste: No

### **SECTION 14: Transport information**

Dangerous goods

No

- 14.1. UN number
- 14.2. UN proper shipping name
- 14.3. Transport hazard class(es)
- 14.4. Packing group
- 14.5. Environmental hazards
- 14.6. Special precautions for user

### 14.7. Maritime transport in bulk according to IMO instruments

### **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

EEC-directive Contains sodium nitrate CAS no. 7631-99-4

This product is regulated by Regulation (EU) 2019/1148. All suspicious

transactions and significant thefts and disappearances should be reported to the

relevant national contact point.

National regulations Quartz – stone dust in the work environment (AFS 2015:2) Waste Ordinance (SFS

2020:614) Hygienic limit values (AFS 2018:1) Chemical Hazards in the Working

Environment (AFS 2011:19)

Biocides No

Nanomaterial No

Legislation and regulations ECHA, European Chemicals Agency, https://echa.europa.eu/sv/home IMA

Europe, Position Paper (February 2010) "Classification and labelling of respirable

crystalline silica (RCS)"

### 15.2. Chemical safety assessment

#### **SECTION 16: Other information**

Supplier's notes

The information is based on our knowledge. However, they do not represent any

Bemix F4 FF - Version 2 Page 11 of 11

	guarantees regarding product characteristics and do not constitute a basis for a contractual legal relationship.	
List of relevant H-phrases (Section 2 and 3)	H272 May intensify fire; oxidiser. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H335 May cause respiratory irritation.	
Key literature references and sources for data	SDS from suppliers ESIS (European Chemical Substances Information System) <a href="http://esis.jrc.ec.europa.eu/">http://esis.jrc.ec.europa.eu/</a> IMA Europe, Position Paper (February 2010) "Classification and labelling of reparabel crystalline silica (RCS)	
Last update date	19.12.2024	
Version	2	
Comments	This version of the Safety data sheet subside all further versions.	